

MS glue special catalyst MS glue catalyst paint catalyst

product name:

MS glue special catalyst, MS glue catalyst, paint catalyst

Similar brands at home and abroad: U-220

Physical properties

Density: 1.21-1.23 (30°C)

Viscosity: 10-50 (mPa.s) (30°C)

Melting point: 15-30°C

Specification

Appearance: yellow oily liquid

Tin content: 27% -28%



What is MS glue:

MS glue is the abbreviation of silane-modified polyether glue. It is mainly a one-component or two-component elastic sealant made of MS polymer as the basic polymer, with fillers, plasticizers and other functional additives. A new generation of construction sealant developed after silicone rubber (SR) and polyurethane rubber (PU). It is mainly used in the fields of bonding, filling, jointing, sealing, waterproofing and reinforcement of construction engineering and decoration. As people's understanding of the advantages of MS glue continues to deepen, its application in the fields of refrigerated trucks, containers, and elevators is also expanding.

MS glue composition:

The main raw materials of MS glue include: alkyl-terminated polyether (MS prepolymer), plasticizer (dioctyl phthalate, referred to as DOP; dibenzyl phthalate, referred to as DCP; dibutyl phthalate) Grease, DBP for short), gas-phase white carbon black, silane coupling agent, catalyst, silane coupling agent, anti-aging additives, dewatering agent, etc.

Characteristics:

This product is a highly active organotin chelated by imported advanced technology. Its activity and catalytic speed are much higher than dibutyltin dilaurate. The curing speed is better than that of dibutyltin acetate, which overcomes the shortcomings of dibutyltin acetate that has a big taste, and has good storage properties in the later stage. For some special products that require relatively fast curing speed, they can be cured quickly, which is better for later construction.

(Note: This product can not be exposed to water)

Use:

1. This product is suitable for two-component polyurethane cross-linked coatings for automotive paints, industrial paints and surface paints.
2. This product is used for room temperature vulcanized silicone rubber, especially suitable for one-component silicone rubber. Its vulcanized products will not return to the original when heated in a sealed state.

Storage:

In a cool and dry warehouse, the lid should be sealed in time after use to reduce contact with air.

Avoid contact with skin and mucous membranes, and rinse with plenty of water immediately after contamination.

Package:

200KG/barrel Storage: It is recommended to store in a dry and cool area with proper ventilation. After the original packaging, please fasten the packaging cover as soon as possible to prevent the product performance from being mixed with other substances such as waterproofing. Store in a cool, dry place, keep the container tightly closed, and avoid contact with oxides. Do not inhale dust and avoid contact with skin and mucous membranes. Smoking, eating and drinking are prohibited in the workplace. After work, take a shower and change clothes. Store contaminated clothes separately and use them after washing. Maintain good hygiene.

Company Name:	Newtop Chemical Materials (Shanghai) Co., Ltd.
Sales Manager:	Hunter
E-Mail:	Hunter@newtopchem.com
Tel:	+86 21-5161 9972
Mobile Phone:	+86-18301903153
Address:	Rm. 1104, No. 258, Songxing West Road, Baoshan District, Shanghai, China (Mainland)

Website:	www.newtopchem.com
----------	--

FAQ

Q1: May I get one sample before placing order?

Re: Yes, Sample are available. For normal products, samples are for free and you just need to bear the freight; For those high value products, you just need to freight and certain product cost. When we both cooperate for some times or when you are our VIP customer, free sample will be offered when you need.

Q2: Which payment is available for your company?

Re: T/T, L/C, You can choose the one which is convenient for you.

Q3: How and when can I get my goods after payment?

Re: For small quantity products, they will be delivered to you by international courier(DHL, FedEx, TNT etc.)

or by air. Usually it will cost 3-5days that you can get the goods after delivery. For large quantity products, shipping by sea is worthwhile. It will cost days to weeks to come to your destination port, which depends on where the port is.

Q4: Is there any possible to use my appointed label or package?

Re: Yes. If needed, we'd like to use label or package according to your requirement.

Q5: How can you guarantee the goods you offer is qualified?

Re: We always believe honesty and responsibility are basis of one company, so whatever products we provide for you all are qualified.